

Características



Basic Parameters	UP2500	US2000B Plus	US3000
Nominal Voltage (V)	24	48	48
Nominal Capacity (Wh)	2840	2400	3552
Usable Capacity (Wh)	2550	2200	3200
Dimension (mm)	442*420*119	442*410*89	442*420*132
Weight (Kg)	27,5	24	32
Discharge Voltage (V)	23~28.8	45 ~ 53.5	45~53.5
Charge Voltage (V)	28.2~28.8	52.5~53.5	52.5~53.5
Charge / Discharge Current (A)	56 (continuous)	25 (Recommended)	37 (Recommended)
	111 (Peak@15s)	50 (Max) 100 (Peak@15s)	74 (Max) 100 (Peak@15s)
Communication Port	RS485	RS232, RS485, CAN	RS232, RS485, CAN
Single string quantity(pcs)		8	12
Working Temperature/℃	0~50	0~50	0~50
Shelf Temperature/℃	-20~60	-20~60	-20~60
Humidity	5%~90%	5%~85%	5%~85%
Altitude (m)	<2000	<2000	<2000
Design life	10+ Years (25℃/77°F)	10+ Years (25℃/77°F)	10+ Years (25℃/77°F)
Cycle Life	>6000, 25℃	>6000, 25℃	>6000, 25℃
Authentication Level	IEC62619/RoHS/UN38.3	TÜV / CE / UN38.3	TÜV / CE / UN38.3